

ABI TM 13/16SL Telescopic Leader

SPECIFICATIONS

Rig Weight	53.5 Tonnes (with MRZV 20VV Vibratory Hammer)
Carrier	SR30T-C
Width of Track (Fixed Track Base)	3.0 Metres
Transport Height (from underside of tracks)	3.3 Metres
Length of Tracks	4.7 Metres
Tail Swing	3.8 Metres

Auto Docking Technology for attachments

WORKING LIMITS

Maximum Pile Length (with MRZV 20VV Vibratory Hammer)	16.0 Metres
Maximum Auger Length (with MDBA 3000 Auger Drive Attachment)	16.4 Metres
Maximum Winch Capacity	5.0 Tonnes
Maximum Pile Weight (Using pitching chain)	3.0 Tonnes



OPTIONAL ATTACHMENTS

- MRZV 20VV Variable Moment Vibratory Hammer (3.950 Tonne)
- MDBA 3000 3.0 Tonnes / Metres Auger Drive (2.1 Tonnes)
- ABI HPU / HPZ Hydropress

SUITABLE APPLICATIONS

- Driving / Extracting Sheet Piles up to 16 Metres in length (as singles or in pairs)
- Pre-Augering
- Impact Driving
- Driving Steel Bearing / Tubular Piles / H-Piles

FOR FURTHER INFORMATION OR TO HIRE ANY OF OUR EQUIPMENT PLEASE CALL

0845 450 7475